

## Switching Power Adaptor

## EWS3065-Series Desktop Type

30 ~65Watts, Single Output



### Features:

- Universal Input Range
- O/P mode: CC,CV
- Protection: Short-circuit, OVP, OCP
- Major applications: Telecom equipments, ITE & AV products, and etc...

### Electrical Data:

1. Universal Input: 90-264VAC 47-63Hz
2. AC input current: 1.6A RMS
3. Load Regulation:  $\pm 5\%$
4. O/P Current: 0Amp Min.
5. MTBF: 35,000Hours
6. Hold Up Time: 10mS



### Mechanical Data:

1. Weight: 330gms
2. Size: 114.0(L)\*53.3(W)\*34.0(H)mm approx
3. Output connector: Optional

### Environmental Data:

1. Operating Temperature: 0°C to 40°C
2. Storage Temperature: -20°C to 85°C
3. Humidity: 5% to 95% non condensing

Model	Power rating (Watt)	O/P Voltage (V)	O/P Current (A) max	Remarks
EWS3065-120250	30	12	2.5	
EWS3065-180167	30	18	1.67	
EWS3065-050800	40	5	8.00	
EWS3065-240167	40	24	1.67	
EWS3065-120350	42	12	3.5	
EWS3065-120375	45	12	3.75	
EWS3065-240188	45	24	1.88	
EWS3065-120417	50	12	4.17	
EWS3065-240208	50	24	2.08	
EWS3065-120500	60	12	5	
EWS3065-240250	60	24	2.5	
EWS3065-120542	65	12	5.42	
EWS3065-240270	65	24	2.7	

**Note:** This form doesn't include the complete model list, if you need output voltage & current different from the above, please feel free to e-mail us via [sales@easyway-electronics.com](mailto:sales@easyway-electronics.com) or [easyway06@gmail.com](mailto:easyway06@gmail.com) .

### EasyWay Electronics Co., Ltd.

Add: Room 201, Flat104,88 Baoming Road, Shanghai, China. Zip: 201101  
 Tel: 86 21 6461 9409 Fax: 86 21 5488 1949  
 E-mail: [sales@easyway-electronics.com](mailto:sales@easyway-electronics.com) <http://www.easyway-electronics.com>